Reviewed on 07/08/2011

Printing date 07/08/2011

1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

Spider Clear · Trade name:

10964 · Article number:

· Application of the substance / the

preparation Maintenance product

· Details of the supplier of the safety data sheet

 Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH

Tel. +49(0)911-642960 Lechstrasse 28 Fax. +49(0)911-644456 D 90451 Nürnberg e-mail info@akemi.de

 Information department: Laboratory

Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH · Emergency telephone number:

Tel. +49(0)911-64296-59

Reachable during the following office hours: Monday – Thursday from 07:30 a.m. to 16:30 p.m.

Friday from 07:30 a.m. to 13:30 p.m.

2 Composition/information on ingredients

· Chemical characterization: Mixtures

Mixture of the substances listed below with nonhazardous additions. · Description:

<u> </u>		
· Dangerous components:		
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1	Naphtha (petroleum), hydrotreated light Xn R65; Xi R38; F R11; N R51/53 R67 Carc. Cat. 2 → H224; H304; H411; H315; H336; H401	50-100%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol R10-67	25-50%
CAS: 8002-74-2 EINECS: 232-315-6	Paraffin waxes and Hydrocarbon waxes	<12.5%
CAS: 64742-82-1 EC number: 919-164-8	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) Xn R65 R52/53-66 ♦ H304; H402; H412	<12.5%
CAS: 110-54-3 EINECS: 203-777-6 Index number: 601-037-00-0	n-hexane Xn R48/20-62-65; Xi R38; F R11; N R51/53 R67 Repr. Cat. 3 → H225; → H361; H373; H304; → H411; → H315; H336	1-5%
CAS: 1589-47-5 EINECS: 216-455-5 Index number: 603-106-00-0	♦ H226; ♦ H360; ♦ H318; ♦ H315; H335	<1%
 Additional information: 	For the wording of the listed risk phrases refer to section 16	

 Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

· Classification of the substance or mixture



H225 Highly flammable liquid and vapour.

(Contd. on page 2)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 1)



GHS08 Health hazard

H304 May be fatal if swallowed and enters airways.



GHS09 Environment

H411 Toxic to aquatic life with long lasting effects.



GHS07

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Harmful

Harmful: may cause lung damage if swallowed.



Irritant

Irritating to skin.



Highly flammable

Highly flammable.



Dangerous for the environment

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

Information concerning particular

hazards for human and

environment:

Vapours of the product are heavier than air and may accumulate on the ground, in mines, drains or college with higher concentration

in mines, drains or cellars with higher concentration.

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

. _ _ _ _ _ _ _ _ _ _ _ _ _ _ _

· Label elements

Labelling according to EU guidelines:

The product has been classified and marked in accordance with directives on hazardous materials.

Code letter and hazard designation of product:







Xn Harmful

F Highly flammable

N Dangerous for the environment

 Hazard-determining components of labelling:

· Risk phrases:

Naphtha (petroleum), hydrotreated light

Highly flammable.

(Contd. on page 3)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 2)

Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness

· Safety phrases: Keep out of the reach of children.

Keep in a cool place.

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe fumes

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

After contact with skin, take off immediately all contaminated clothing, and wash

immediately with plenty of water and soap.

Do not empty into drains, dispose of this material and its container at hazardous

or special waste collection point

Take precautionary measures against static discharges.

Wear suitable protective clothing, gloves and eye/face protection. In case of insufficient ventilation, wear suitable respiratory equipment.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

· Classification system:

· NFPA ratings (scale 0 - 4)

1 0

Health = 1 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *1 Fire = 3 Reactivity = 0

4 First aid measures

· Information for doctor:

• **General information:** Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

Symptoms of poisoning may even occur after several hours; therefore medical

observation for at least 48 hours after the accident.

Position and transport stably on side.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for

transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a

doctor.

• After swallowing: Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Symptoms in intoxication with (aromatic) hydrocarbons (dosis letalis about 30 g)

a) In acute intoxication: headache, dizziness, euphoria, gastro-intestinal

dysfunction, state of excitement, coma.

b) In chronic intoxication: myelotoxic damage, fatigue, dizziness, emaciation,

cardiac palpitation after physical exercise, leucopenia, anemia, leukosis.

Therapy in hydrocarbons intoxication: In case of inhalation provision of fresh air; in case of peroral intake administration of Carbo medicinalis; only after intubation conduct of gastrolavage in application of Carbo medicinalis; in case of

cramps administration of Diazepam 20 mg intravenously.

(Contd. on page 4)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 3)

<u>Danger</u> Danger of impaired breathing.

5 Firefighting measures

· Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or

alcohol resistant foam.

For safety reasons unsuitable

extinguishing agents:

Water with full jet

Special hazards arising from the

substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

In certain fire conditions, traces of other toxic gases cannot be excluded.

• **Protective equipment:** Wear self-contained respiatory protective device.

Wear fully protective suit.

Do not inhale explosion gases or combustion gases.

• Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with

official regulations.

Collect contaminated fire fighting water separately. It must not enter the sewage

system.

6 Accidental release measures

· Personal precautions, protective

equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation Keep away from ignition sources

Use respiratory protective device against the effects of fumes/dust/aerosol.

• Environmental precautions: Inform respective authorities in case of seepage into water course or sewage

system.

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal

binders, sawdust).

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

• Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

Precautions for safe handling
 Keep receptacles tightly sealed.

Ensure good ventilation/exhaustion at the workplace. Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier

than air).

Use only in well ventilated areas.

 Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Protect from heat.

(Contd. on page 5)



Reviewed on 07/08/2011 Printing date 07/08/2011

Trade name: Spider Clear

(Contd. of page 4)

Highly volatile, flammable constituents are released during processing.

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in the original receptacle. Prevent any seepage into the ground.

Information about storage in one

common storage facility:

Store away from oxidizing agents. Store away from foodstuffs.

· Further information about storage

conditions:

Store in cool, dry conditions in well sealed receptacles.

Keep receptacle tightly sealed. Protect from heat and direct sunlight. Store receptacle in a well ventilated area.

8 Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see item 7.

· Components with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

REL Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm

TLV Short-term value: 553 mg/m³, 150 ppm Long-term value: 369 mg/m³, 100 ppm

8002-74-2 Paraffin waxes and Hydrocarbon waxes

REL 2 mg/m³

TLV 2 mg/m³

110-54-3 n-hexane

PEL 1800 mg/m³, 500 ppm REL 180 mg/m³, 50 ppm 176 mg/m³, 50 ppm TLV

Skin: BEI

Additional information:

The lists that were valid during the creation were used as basis.

· Personal protective equipment:

General protective and hygienic

measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin. Do not inhale gases / fumes / aerosols. Do not eat, drink, smoke or sniff while working. Use skin protection cream for skin protection.

Clean skin thoroughly immediately after handling the product.

· Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of

intensive or longer exposure use respiratory protective device that is

independent of circulating air.

Short term filter device:

Filter AX

· Protection of hands: Preventive skin protection by use of skin-protecting agents is recommended.

After use of gloves apply skin-cleaning agents and skin cosmetics.

Akemi skin protection agent recommendation for preventive skin shelter without

use of protective gloves:

STOKODERM (http://www.stoko.com)

(Contd. on page 6)

- USA



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 5)

Akemi skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:

STOKO EMULSION (http://www.stoko.com)

Akemi skin protection recommendation for skin cleaning after product handling: FRAPANTOL (http://www.stoko.com)

Akemi skin protection agent recommendation for skin aftercare:

STOKO VITAN (http://www.stoko.com)



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times´ data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.

This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).

Material of gloves

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the

protective gloves and has to be observed. Value for the permeation: Level \geq 6, 480 min

 For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

Nitrile rubber, NBR

Camatril (KCL, Art No. 730, 731, 732, 733)

 As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton) Vitoject (KCL, Art No. 890)

Nitrile rubber, NBR

Camatril (KCL, 730, 731, 732, 733)

 Not suitable are gloves made of the following materials:

Leather gloves Strong gloves

· Eye protection:



Tightly sealed goggles

Body protection:

Protective work clothing

(Contd. on page 7)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

· General Information

(Contd. of page 6)

9 Physical and chemical properties

Appearance:
Form:
Color:
Odor:
Petrol-like

· **pH-value:** Not applicable

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 316°C (601 °F)

• Flash point: -18°C (-0 °F)

· <u>Ignition temperature:</u> 270°C (518 °F)

• Auto igniting: Product is not selfigniting.

• <u>Danger of explosion:</u> Product is not explosive. However, formation of explosive air/vapor mixtures are

possible.

· Explosion limits:

<u>Lower:</u> 2.3 Vol % Upper: 6.5 Vol %

· Vapor pressure at 20°C (68 °F): 12 hPa (9 mm Hg)

• **Density at 20°C (68 °F):** 0.78 g/cm³ (6.509 lbs/gal)

- Specific gravity at 20°C (68 °F): 0.78 g/cm³ (6.509 lbs/gal)

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Viscosity:

<u>Dynamic:</u> Not determined. Kinematic at 20°C (68 °F): 11 s (DIN 53211/4)

· Solvent content:

Organic solvents: 87.1 %

10 Stability and reactivity

· Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

No decomposition if used and stored according to specifications.

· Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Flammable gases/vapors

11 Toxicological information

· Acute toxicity:

- LD/LC50 values that are relevant for classification:				
64742-49-0 Naphtha (petroleum), hydrotreated light				
Oral	LD50	> 5000 mg/kg (rat)		
Dermal	LD50	> 2000 mg/kg (rat)		
Inhalative	LC50/4 h	> 2.0 mg/l (rat)		

(Contd. on page 8)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 7)

64742-82-1 Hydrocarbons,	C10-C13, n-alkanes,	isoalkanes, cyclics	, aromatics (2-25%)
--------------------------	---------------------	---------------------	---------------------

Dermal LD50 >2920 mg/kg (rabbit) (OECD-Prüfrichtlinie 402)

110-54-3 n-hexane

 Oral
 LD50
 28700 mg/kg (rat)

 Dermal
 LD50
 3295 mg/kg (rabbit)

· Primary irritant effect:

· on the skin: Irritant to skin and mucous membranes.

· on the eye: No irritating effect.

Sensitization: No sensitizing effects known.

· Additional toxicological

information: The product shows the following dangers according to internally approved

calculation methods for preparations:

Harmful Irritant

12 Ecological information

Acquatic toxicity:

64742-82-1 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

EL50/72h 50-100 mg/l (Pseudokirchneriella subcapitata)

LL50/96h 10-100 mg/l (Oncorhynchus mykiss)

Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

• General notes: Do not allow undiluted product or large quantities of it to reach ground water,

water course or sewage system.

Water hazard class 1 (Self-assessment): slightly hazardous for water

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

Waste treatment methods

Recommendation: Must not be disposed of together with household garbage. Do not allow product

to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

Empty contaminated packagings thoroughly. They can be recycled after

thorough and proper cleaning.

Recommended cleansing agent: Alcohol

14 Transport information

· DOT regulations:



· Hazard class:

· Identification number: UN3295

Packing group:

• Proper shipping name (technical name): HYDROCARBONS, LIQUID, N.O.S.

3

(Contd. on page 9)



Reviewed on 07/08/2011 Printing date 07/08/2011

Trade name: Spider Clear

(Contd. of page 8)

Label

· Land transport ADR/RID (cross-border):





· ADR/RID class: 3 (F1) Flammable liquids

· Danger code (Kemler): 33 3295 · UN-Number: · Packaging group: Ш

· Special marking: Symbol (fish and tree)

3295 HYDROCARBONS, LIQUID, N.O.S., special provision 640D, · UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS

· Maritime transport IMDG:





IMDG Class: 3295 UN Number: Label 3 Packaging group: Ш F-E,S-D EMS Number:

Marine pollutant:

Symbol (fish and tree)

HYDROCARBONS, LIQUID, N.O.S. Propper shipping name:

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3295 · UN/ID Number: · Label 3 · Packaging group:

· Propper shipping name: HYDROCARBONS, LIQUID, N.O.S.

· UN "Model Regulation":

UN3295, HYDROCARBONS, LIQUID, N.O.S., ENVIRONMENTALLY

HAZARDOUS, 3, II

· Environmental hazards: Product contains environmentally hazardous substances:

15 Regulatory information

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

Section 313 (Specific toxic chemical listings):

110-54-3 n-hexane

· TSCA (Toxic Substances Control Act):

64742-49-0 Naphtha (petroleum), hydrotreated light

107-98-2 1-methoxy-2-propanol

(Contd. on page 10)



Printing date 07/08/2011 Reviewed on 07/08/2011

Trade name: Spider Clear

(Contd. of page 9)

8002-74-2 Paraffin waxes and Hydrocarbon waxes

68132-00-3 Kohlenwasserstoff-Harz

110-54-3 n-hexane

1589-47-5 2-methoxypropanol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

110-54-3 n-hexane

II

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· MAK (German Maximum Workplace Concentration)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:







Xn Harmful

F Highly flammable

N Dangerous for the environment

Hazard-determining components

of labelling:

Naphtha (petroleum), hydrotreated light

• Risk phrases: Highly flammable.

Irritating to skin.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

Harmful: may cause lung damage if swallowed. Vapours may cause drowsiness and dizziness

- Safety phrases: Keep out of the reach of children.

Keep in a cool place.

Keep container in a well-ventilated place.

Keep away from sources of ignition - No smoking.

Do not breathe fumes

(Contd. on page 11)



Reviewed on 07/08/2011 Printing date 07/08/2011

Trade name: Spider Clear

(Contd. of page 10)

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Do not empty into drains, dispose of this material and its container at hazardous

or special waste collection point

Take precautionary measures against static discharges.

Wear suitable protective clothing, gloves and eye/face protection. In case of insufficient ventilation, wear suitable respiratory equipment.

If swallowed, seek medical advice immediately and show this container or label.

Use only in well-ventilated areas.

· National regulations:

· Information about limitation of use: Employment restrictions concerning young persons must be observed.

Employment restrictions concerning pregnant and lactating women must be

observed.

· Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

· VOC USA 632.6 g/l / 5.28 lb/gl

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: Laboratory · Contact: Elke Hake

Fon ++49 (0)911 64296-59 @mail E.Hake@akemi.de

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European · Abbreviations and acronyms:

Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent