

511 Spray-On Grout Sealer

Natural Look Penetrating Sealer

Water & Stain Protection for

- New Grout
- Natural Stone
- Old Grout

Will not Harm Ceramic Tile, Porcelain Tile, Glazed Tile, Quarry Tile, Glass or Plastic Tile, Marble, Granite, Limestone, Travertine, Slate, other Natural Stone

Uses

- Interior & Exterior
- Restrooms
- Kitchen
- Anywhere you use Grout
- Showers

Special Features

- Easy To Use "Clean Hands" Approach
- Apply as little as 2 hours after Grouting
- Low Toxicity
- Stain Resistant
- Economical
- Recyclable (doesn't end up in a landfill)
- Directional Spray
- Weather Resistant
- Non Yellowing
- U.V. Transparent
- Tamper Proof Container

KEEP OUT OF REACH OF CHILDREN. This product is formulated for sealing all types of new and old grout to provide resistance against water, oils, alkalis, acids, and staining. **511 Spray-On Grout Sealer** is a unique formulation designed for the protection of all types of grout both new and old. **511 Spray-On Grout Sealer** penetrates into the surface and forms an invisible barrier that is resistant to moisture and stains, while allowing vapor to escape. **511 Spray-On Grout Sealer** is not a surface coating and will not alter the natural look while making the grout easier to clean. **511 Spray-On Grout Sealer** can be applied to freshly installed grout as quickly as 2 hours after grouting. **511 Spray-On Grout Sealer** can be used on interior and exterior applications. **511 Spray-On Grout Sealer** is U.V. transparent and will not yellow under any circumstances. **511 Spray-On Grout Sealer** averages five to twenty times the coverage of competitive products. (See coverage chart). **511 Spray-On Grout Sealer** uses a "Clean Hands" approach to grout sealer application and has a unique directional spray allowing the user to apply the sealer without touching their hands.

Test Data

511 Spray-On Grout Sealer HAS BEEN TESTED BY SCIENTIFIC CERTIFICATION SYSTEMS PASSING THE MOST STRINGENT CALIFORNIA AIR RESOURCES BOARD (CARB) SECTION 01350 TEST AND HAS RECEIVED INDOOR ADVANTAGE GOLD CERTIFICATION.

Sample Testing

Due to the differences of each grout, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

Color Enhancement

For added color with "TEXTURED AND NON POLISHED" surfaces, **511 Seal & Enhance** may be applied as directed.

Gloss Enhancement

For a higher gloss finish on POLISHED stone surfaces, use **Water Ring & Etch Remover**, **Marble Conditioner**, **Mira Dust**, **Mira Polish** or **Granite Brite**. For counters and furniture, use **Stone Polish**. For tile surfaces, try **Tile Brite**.

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non-masonry surfaces.

NEW INSTALLATIONS - APPLICATION INSTRUCTIONS

Read entire label and PDS/MSDS before using. **511 Spray-On Grout Sealer** should not be diluted or thinned in any way. **511 Spray-On Grout Sealer** should be used as is direct from approved container.

After Grouting: Once grouted, make sure that all grout residue is removed from the surface with a clean sponge and water. Allow grout to cure per manufacturers specification or at least 2 hours. If grout clean up is not performed effectively, an additional cleaning may be necessary to remove remaining grout residue or haze. For this procedure use **Phosphoric Acid Cleaner**, (HDAC) **Heavy Duty Acidic Cleaner (Hydrochloric Acid)** or **Epoxy Grout Film Remover** following the instructions carefully. Once the cleaned area has completely dried, proceed with the sealing of the grout for water and stain resistance. Apply **511 Spray-On Grout Sealer** to all grout with the unique "Clean Hands" Spray. Any excess sealer that gets on the surface should be wiped off with a clean towel before it dries.

Existing Installation - Surface Preparation

Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust and other heavy dirt and grime.

Surface Coating/Wax Removal: To remove existing coatings and/or waxes, use **Mira Strip** or **Finish Sealer Stripper** as directed.

Heavy Duty Cleaning: To remove lime and hard water deposits, efflorescence, rust, grease and other heavy dirt and grime use **HDAC (Heavy Duty Acidic Cleaner)** or **Phosphoric Acid Cleaner** as directed.

For a non-acid deep clean use **Liquid Powlitice** as directed.

Light Cleaning: Use **Tile & Stone Cleaner**, **Porcelain & Ceramic Tile Cleaner**, **Limestone/Travertine Soap** or **Counter Kleen** as directed.

Existing Installation - Application Instructions

Once all grout and surrounding surfaces are clean, proceed with the application instructions previously mentioned.

Residue Removal

To remove accumulated **511 Spray-On Grout Sealer**, use **Miracle Residue Remover** as directed.

Cure Time

511 Spray-On Grout Sealer will be dry to the touch in 1 - 3 hours and may be used for normal foot traffic. For optimum results the area should be kept dry and free from staining materials for 72 hours.

Coverage: Used as directed, **511 Spray-On Grout Sealer** will cover up to 250 linear feet of grout.

Cost per linear foot: Approximately 5 cents per foot.

MAINTENANCE

For ongoing maintenance instructions please refer to Miracle Sealants Care Guide. Refer to the Miracle Sealants Product Recommendation Chart for specific product recommendations.

Storage

Store **511 Spray-On Grout Sealer** in the original sealed container. Stored at 77° F (25° C), **511 Spray-On Grout Sealer** will have a shelf life of 12 months.

Technical Support

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

Office Hours

Monday - Friday from 8:30 am - 5:00 pm PT.
1-626-443-6433 1-800-350-1901 • Fax: 1-626-443-1435

Website: www.miraclesealants.com

Product Damaged During Transportation

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

Additional Product

Miracle Sealants Company offers a complete line of water and stain repellents, sealers, cleaners, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it-yourself specialist.

Warranty

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein. Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

Caution

511 Spray-On Grout Sealer contains combustible petroleum distillates. All solvents must be considered toxic and must be used in a well-ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of the area until product or surface has thoroughly dried. Refer to the MSDS for additional information.



Safety Data Sheet

Issue Date: 01-Nov-2013

Revision Date: 16-Apr-2014

Version 1

1. IDENTIFICATION

Product Identifier

Product Name 511 Spray-On Grout Sealer

Other means of identification

SDS # MSC-036

Product Code OMB No. 1218-0072
UN/ID No UN1950

Recommended use of the chemical and restrictions on use

Recommended Use Grout sealer. Water, Stain & Slip Protection for: Quarry Tile, Ceramic Tile, Porcelain Tile, Glazed Tile, Marble, Granite, Travertine, Slate, Grout, Quartz, Brick, Terrazzo.

Details of the supplier of the safety data sheet

Supplier Address
Miracle Sealants Company
12318 Lower Azusa Road
Arcadia, CA 91006

Emergency Telephone Number

Company Phone Number 1-626-443-6433 (Phone)
1-626-443-1435 (Fax)

24 Hour Emergency Phone Number 1-800-350-1901

Emergency Telephone (24 hr) For product spills, leaks or exposures call:
Infotrac 1-800-535-5053 (North America) or 1-352-323-3500 (International)

2. HAZARDS IDENTIFICATION

Appearance Clear, colorless

Physical State Aerosol

Odor Aromatic

Classification

Acute toxicity - Inhalation (Vapors)	Category 3
Germ cell mutagenicity	Category 1B
Aspiration toxicity	Category 1
Flammable Aerosols	Category 1

Hazards Not Otherwise Classified (HNOC)

May be harmful in contact with skin

Signal Word

Danger

Hazard Statements

Toxic if inhaled
May cause genetic defects
May be fatal if swallowed and enters airways
Extremely flammable aerosol



Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do not induce vomiting

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed
 Protect from sunlight

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Petroleum Distillate	64742-88-7	Proprietary
Hydrocarbon Propellant	68476-86-8	Proprietary

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Product contains a proprietary mixture of ingredients.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists.
Skin Contact	Remove contaminated clothing and launder before reuse. Wash with soap and water. Get medical attention if irritation persists.
Inhalation	If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Seek medical attention.
Ingestion	IF SWALLOWED: call a poison control center or physician immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

Most important symptoms and effects**Symptoms**

Eyes: Causes severe eye irritation
 Skin: Causes mild skin irritation, drying of the skin. May cause an allergic skin reaction.
 Ingestion: Can be harmful if swallowed. Causes vomiting, nausea and diarrhea.
 Inhalation: Excessive inhalation causes headache, dizziness, nausea and incoordination.
 Toxic if inhaled.

Medical conditions aggravated: Respiratory, pulmonary, liver and kidney disorders. Central nervous systems disorders. Gastrointestinal disorders.

Indication of any immediate medical attention and special treatment needed**Notes to Physician**

Medical conditions aggravated: Respiratory, pulmonary, liver and kidney disorders. Central nervous systems disorders. Gastrointestinal disorders.

5. FIRE-FIGHTING MEASURES**Suitable Extinguishing Media**

Foam. Dry chemical. Water spray (fog).

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Extremely flammable. This product releases Flammable Vapors at well below ambient temperatures and readily forms flammable mixtures with air exposed to an ignition source. It will burn in the open or be explosive in confined spaces. Its vapors are heavier than air and may travel long distances to a point of ignition, and then flash back. Alkaline/chlorine gas mixtures have produced explosions.

Hazardous Combustion Products Carbon monoxide, carbon dioxide, silicone dioxide, fumes of xylene, aromatic and aliphatic hydrocarbons.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool exposed containers with water to prevent rupturing. Gas fires should not be extinguished unless the gas flow can be stopped immediately. Allow the fire to burn itself out. If the source cannot be shut off immediately, all equipment and surfaces exposed to the fire should be cooled with water to prevent over-heating, flash-backs, or explosions. Control fire until gas supply can be shut off. Use proper protective equipment. Use fresh air respirator when exposure to hazardous concentrations of toxic gases is possible.

Fire Fighting: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Use foam, dry chemical, or water spray to extinguish fire. Avoid spraying water directly into storage containers due to danger of boiling over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition sources where they may ignite or explode.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures****Personal Precautions**

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).
 Wear protective clothing as described in Section 8 of this safety data sheet. Ventilate affected area.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up**Methods for Containment**

Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up

Steps to be taken in case material is released or spilled: wipe, scrape or soak up in an inert material and put in a container for disposal. Use clean non-sparking tools to collect absorbed material. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling

Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Keep out of the reach of children. Wash face, hands, and any exposed skin thoroughly after handling. Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Avoid breathing vapors or mists. Use only with adequate ventilation. Keep container tightly closed. Ground container and transfer equipment to eliminate static electric sparks. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Keep cool. Warning : Never expose can or content to open flame. Do not puncture pressurized can. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Precautions to be taken in handling and storing: use a ground strap. Store upright in a cool place below 77° F (25° C). Keep out of the reach of children. Store locked up. Protect from sunlight.

Incompatible Materials

Strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

The following information is given as general guidance

Appropriate engineering controls

Engineering Controls

Local exhaust: Recommended
Mechanical exhaust: General ventilation system should be provided.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight fitting, splash proof safety goggles.

Skin and Body Protection

Protective gloves: Plastic or rubber, chemical resistant
Protective clothing or equipment: Chemical resistant clothing.

Respiratory Protection

Ventilate by opening all doors and windows. If exposure above the TLV or PEL require a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CFR 1910.134 is required.

General Hygiene Considerations

Work hygienic practices: Wash hands thoroughly before handling foodstuffs, liquids or tobacco products. Use common sense and care around chemicals. Never mix this product with other chemicals. Consult your supervisor for all other hygienic and safety practices. All practices depend on your specific business. Directions for use normally found on label which will dictate engineering and control measures.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State
Appearance
Color

Aerosol
Clear, colorless
Colorless

Odor
Odor Threshold

Aromatic
Not determined

Property

Values

Remarks • Method

pH
Melting Point/Freezing Point
Boiling Point/Boiling Range
Flash Point
Evaporation Rate
Flammability (Solid, Gas)
Upper Flammability Limits

Neutral
Not available
355-395 °F / 179.44-201.66 °C
Level 3 Aerosol
<0.1
Not applicable
7%

Lower Flammability Limit	1%	
Vapor Pressure	.5 mmHg	@ 20 C
Vapor Density	5.3	(Air=1)
Specific Gravity	0.80	
Water Solubility	insoluble	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Auto-ignition Temperature	Not determined	
Decomposition Temperature	Not determined	
Kinematic Viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	
VOC Content	727 g/L	
Density	798 Kg/M3	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from sources of ignition such as heat, sparks or open flames.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide, silicone dioxide, fumes of xylene, aromatic and aliphatic hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact	Avoid contact with eyes.
Skin Contact	May be harmful in contact with skin.
Inhalation	Toxic if inhaled.
Ingestion	May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum Distillate 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity	May cause genetic defects.
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

Legend

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum Distillate 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static		100: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Hydrocarbon Propellant 68476-86-8	2.8

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

IATA

UN/ID No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1

IMDG

UN/ID No UN1950
Proper Shipping Name Aerosols

Hazard Class 2.1
Marine Pollutant This material may meet the definition of a marine pollutant

TDG

UN/ID No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1

15. REGULATORY INFORMATION

International Inventories

TSCA Listed

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*

US Federal Regulations

SARA 313

Not determined

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Petroleum Distillate 64742-88-7	X		

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	2	3	0	None
HMIS	Health Hazards	Flammability	Physical Hazards	Personal Protection
	2	3	0	Not determined

Issue Date: 01-Nov-2013
Revision Date: 16-Apr-2014
Revision Note: New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet